

CLAIMS

1. A system for providing an automatic reply to a first electromagnetic signal comprising:

first means for receiving said first electromagnetic signal;

second means for analyzing said electromagnetic signal to extract data with
5 respect thereto;

third means responsive to said data for synthesizing a second electromagnetic signal; and

fourth means for automatically transmitting said second electromagnetic signal.

2. The invention of Claim 1 further including a wake-up circuit.

3. The invention of Claim 1 wherein said first and second electromagnetic signals are radio frequency signals.

4. The invention of Claim 3 wherein said first means is a radio frequency receiver.

5. The invention of Claim 4 wherein said radio frequency receiver is a narrow band receiver or a narrow band mode of a variable bandwidth receiver.

6. The invention of Claim 4 wherein said first and said second means comprise means for tracking said first electromagnetic signal.

7. The invention of Claim 6 wherein said second means includes a down converter.

8. The invention of Claim 7 wherein said down converter includes a first mixer driven by a local oscillator circuit.

9. The invention of Claim 8 wherein said second means further includes a programmable filter connected to the output of said mixer.

10. The invention of Claim 9 wherein said second means further includes an analog to digital converter connected to the output of said filter, to include a programmable data rate analog to digital converter.

11. The invention of Claim 10 wherein said second means further includes a digital signal processor connected to the output of said analog to digital converter.

12. The invention of Claim 11 wherein said second means includes a data processor.

13. The invention of Claim 12 wherein said data processor includes a microprocessor.

14. The invention of Claim 13 wherein said second means includes software adapted for execution by said microprocessor.

15. The invention of Claim 14 wherein said software includes code for tracking said first electromagnetic signal and providing said data with respect thereto.

16. The invention of Claim 14 wherein said software includes code for identifying a timing characteristic of said first electromagnetic signal and providing said data with respect thereto.

17. The invention of Claim 14 wherein said software includes code for identifying a format of said first electromagnetic signal and providing said data with respect thereto.

18. The invention of Claim 1 wherein said third means includes a data processor.

19. The invention of Claim 18 wherein said data processor includes a microprocessor.

20. The invention of Claim 19 wherein said third means includes software adapted for execution by said microprocessor.

21. The invention of Claim 20 wherein said third means includes a digital signal processor.

22. The invention of Claim 21 wherein said digital signal processor is a field programmable gate array.

23. The invention of Claim 21 wherein said third means further includes a digital to analog converter.

24. The invention of Claim 23 wherein said third means further includes a programmable filter.

34. The invention of Claim 32 wherein said user data includes video data.

35. The invention of Claim 32 wherein said user data includes position data.

36. The invention of Claim 35 wherein said position data is Global Positioning System data.

37. The invention of Claim 31 further including means for extracting user data from said first electromagnetic signal and outputting said user data via said external interface.

38. The invention of Claim 1 wherein said first electromagnetic signal is optical.

39. The invention of Claim 38 wherein said first electromagnetic signal is infrared.

40. The invention of Claim 1 wherein said second electromagnetic signal is optical.

41. The invention of Claim 40 wherein said second electromagnetic signal is infrared.

42. A digital radio frequency tag comprising:
a radio frequency receiver adapted to receive a first radio frequency signal;
a data processor connected to said receiver and adapted to provide data in response to said first radio frequency signal;

